



MATERIAL SAFETY DATA SHEET

CLOCK LUBE

PCN(s) 136

Publication Date: 8/15/11

REV: H

1. SUPPLIER AND EMERGENCY INFORMATION Emergency Phone Numbers:

L&R Manufacturing Company
577 Elm Street, P.O. Box 607
Kearny, NJ 07032 - 0607 USA

Product Information
Call: **201-991-5330**
www.lrultrasonics.com

For emergencies involving a spill, leak,
fire or accident contact:
CHEMTREC - 800-424-9300
within the United States or (01)**703-527-3887** [USA] for
International collect calls

2. HAZARDS IDENTIFICATION

Physical appearance and odor: Clear Blue liquid with characteristic odor.

A: WARNING STATEMENT: FLAMMABLE LIQUID

Acute Eyes: Direct contact causes irritation, redness and possible tearing.

Acute Skin: Prolonged or repeated contact causes redness, and drying of the skin..

Acute Inhalation: Breathing high concentrations of vapors or mists may cause irritation to the nose and may cause drowsiness.

B: POTENTIAL HEALTH EFFECTS:

Acute Ingestion: Not known, but expected to cause nausea and diarrhea.

Chronic Effects: This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogen.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Number	Percentage
Mineral Spirits (C ₆ H ₆ < 0.1%)	8052-41-3	65-80
Solvent Naphtha Light Aliphatic	64742-89-8	15-30
Polydimethylsiloxanes	63148-62-9	0.5-4.0
Mineral Oil	8042-47-5	0.5-2.0
Xylene	1330- 20 -9	1 - 5

4. FIRST AID MEASURES

Eye Exposure: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention.

Skin Exposure: Wash thoroughly with water. If irritation or redness develops, seek medical attention.

Inhalation: If respiratory irritation or distress occurs, move victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

Ingestion: If large quantities are ingested (more than 5 ounces in an adult), induce vomiting, preferably with syrup of Ipecac under the direction of a physician or poison center.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Skin contact may aggravate existing skin disease.

5. FIRE FIGHTING MEASURES

FIRE HAZARD DATA: FLAMMABLE LIQUID

Suitable Extinguishing Media: Extinguish with dry chemical, CO₂ or a BC/ABC extinguisher.

Unsuitable Extinguishing Media: Do not use a solid stream of water, since the stream will scatter and spread the fire.

Water spray may be used to keep fire exposed containers cool.

Special Fire Fighting Procedures: Wear full protective clothing and self-contained breathing apparatus (SCBA) approved for fire fighting.

Unusual Fire and Explosion Hazards: Closed containers may explode due to build up of pressure when exposed to extreme heat.

Hazardous Decomposition Materials: (under fire conditions) Oxides of nitrogen and carbon.

6. ACCIDENTAL RELEASE MEASURES

Cleanup and Disposal of Spill: Ventilate area of spill. Use non-reactive material to pick up spill. Dispose of in accordance with local, state and federal regulations.

Environmental and Regulatory Reporting: Not required

7. HANDLING AND STORAGE

Minimum/Maximum Storage Temperatures: 39 to 100 ° F.

HANDLING: AVOID CONTACT WITH SKIN, EYES OR CLOTHING

8. EXPOSURE CONTROL/PERSONAL PROTECTION

General: These recommendations provide general guidance for handling of this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. When developing safe handling procedures, do not overlook the need to clean and dispose of the material. Waste resulting from the use of this product should be handled in accordance with Section 13: Disposal Considerations.

Exposure Guidelines: Exposure limits are recommended worker breathing limits. The following limits apply to this material:

INGREDIENTS

Mineral Spirits 100 ppm OSHA/ TWA
 Polydimethylsiloxane None established
 Xylene 100 ppm ACGIH TWA

LIMITS**INGREDIENTS**

Solvent Naphtha
 Mineral oil

LIMITS

300 ppm OSHA/ ACGIH TWA
 None established

Engineering Controls: Provide adequate room ventilation.

Respiratory Controls: For reasonable uses of this material, respiratory protection should not be necessary.

Eye/Face Protection: Safety glasses to protect from splashing.

Skin Protection: Wear Rubber or plastic gloves to avoid drying and irritation to the skin.

Work Practice Control: Normal hygiene in the work area should be taken when working with or handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Clear Liquid

pH: Not Established

Water Solubility: Not Soluble

Freezing Point Range: Not Established

Vapor Pressure: Not available

Flash Point: 81 - 83 °F (27-28° C) **Method:** Tag Closed

Flammability limits (vol/vol %): Lower: No Data Upper: No Data

Percent volatile by volume: Approx. 90 % by volume **V.O.C. (calculated):** 6.28 lbs/gal or 752.6 g/l

Color: Blue

Specific Gravity: 0.81

Melting Point Range: Not applicable

Boiling Point: >212°F

Vapor Density: Not available

Odor: Characteristic

Odor Threshold: Not available

Evaporation Rate: Not available

Partition Coefficient; n-octanol / water: Not available

Decomposition Temperature: Not available

Auto Ignition Temperature: Not available

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to be avoided: Keep away from heat and open flames

Materials/Chemicals to be avoided: Strong Acids.

Hazardous Decomposition Products: Thermal Oxides of carbon and nitrogen

Possibility of Hazardous Reactions: WILL NOT OCCUR

11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation: Irritating to eyes.

Acute Skin Irritation: No test data found for product.

Acute Dermal Toxicity: No test data found for product.

Acute Respiratory Irritation: No test data found for product.

Acute Inhalation Toxicity: No test data found for product.

Acute Oral Toxicity LD50 (rat): Mineral Spirits > 5 gm/kg

Polydiethylsiloxanes = 2840 mg /kg

Mineral oil = 5000 mg / kg

Solvent Naphtha > 8,000 mg/kg

Xylene = 4300 mg/kg

Chronic Toxicity: This product does not contain any substances that are considered by OSHA, NTP, IARC OR ACGIH to be a probable or suspected human carcinogen. No additional test data was found for this product.

12. ECOLOGICAL INFORMATION

Ecotoxicological Information: No data found.

13. DISPOSAL CONSIDERATIONS

This material is a flammable liquid and must be disposed in accordance with all local, state and federal regulations. IT CAN NOT BE DISPOSED OF IN A SANITARY SEWER SYSTEM.

14. TRANSPORTATION INFORMATION

This product is classified as a flammable liquid for domestic shipments per 49 CFR . For domestic ground shipments of containers of 1 gallon or less, it is listed as ORM-D. For all other containers: Flammable Liquid n.o.s. (Contains Naphtha, Petroleum), UN 1993, Packing Group III. Do not stack cartons more than five high.

15. REGULATORY INFORMATION

Inventory Issues: All components of this product are listed on the U.S. TSCA, Canadian DSL, European EINECS/ELINS chemical listings

16. OTHER INFORMATION**National Fire Protection Association**

Hazard Rating, NFPA

Health

Flammability

Reactivity

Special

2

3

0

--

MSDS CHANGES

REV

G

H

DATE

5/9/08

8/15/11

DESCRIPTION OF CHANGE

Updated CAS# and Chemical Description

Reviewed/Updated

Disclaimer: The information herein is given in good faith but no warranty expressed or implied is made.

Prepared By: L&R Manufacturing Company
 Product Name: **CLOCK LUBE**

Date: 8/15/11