



MATERIAL SAFETY DATA SHEET

HYDRO-SONIC CLEANING SOLUTION NON-AMMONIATED

PCN(s): 110, 111

Publication Date 11/17/05

REV: E

1. SUPPLIER AND EMERGENCY INFORMATION

L&R Manufacturing Company
577 Elm Street, P.O. Box 607
Kearny, NJ 07032 - 0607 USA

Product Information
Call: 201-991-5330

Emergency Phone Numbers:

For emergencies involving a spill, leak, fire or accident contact:
CHEMTREC - 800-424-9300
within the United States or 703-527-3887
for international collect calls.

2. COMPOSITION/INFORMATION ON INGREDIENT

Component	CAS Number	Percentage
WATER	7732-18-5	45-55
OLEIC ACID	112-80-1	1- 5
TERPENE HYDROCARBONS	BLEND N/A	10-20
2- PROPOXYETHANOL	2807-30-9	20-25
QUATERNARY AMMONIUM CHLORIDE	68610-19-5	1 - 5
DODECYLTHIOETHOXYLATE	9004-83-5	1 - 5
MONOETHANOLAMINE	141-43-5	1 - 5
SODIUM DODECYLBENZENE SULFONATE	25155-30-0	1 - 5
NONYLPHENOXYPOLYETHANOI	9016-45-9	1 - 5

3. HAZARDS IDENTIFICATION

Physical appearance and odor: Clear amber liquid with mild pine odor.

A: WARNING STATEMENT:

Good industrial hygiene practices should be used when handling this material.

Acute Eyes: Direct contact causes irritation, redness and possible tearing. Use good ventilation to minimize exposure.

Acute Skin: Prolonged or repeated contact causes redness, and drying of the skin.

Acute Inhalation: Breathing high concentrations of vapors or mists will cause irritation to the respiratory tract.

B: POTENTIAL HEALTH EFFECTS:

Acute Ingestion: Will cause irritation to the digestive tract and signs of nervous system depression.

Chronic Effects: This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogens.

4. FIRST AID MEASURES

Eye Exposure: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention.

Skin Exposure: Wash thoroughly with water. If irritation or redness develops, seek medical attention.

Inhalation: If respiratory irritation or distress occurs, move victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

Ingestion: Seek immediate medical attention. DO NOT INDUCE VOMITING.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Skin contact may aggravate existing skin disease.

5. FIRE FIGHTING MEASURES

FIRE HAZARD DATA:

FLASH POINT: 117 °F (47.2 °C)

METHOD USED: Tag Closed Cup

Flammability limits (vol/vol%) : Lower: No Data Upper: No Data

Extinguishing Media: Extinguish with dry chemical, CO₂ or a BC/ABC extinguisher.

Special Fire Fighting Procedures: None known

Unusual Fire and Explosion Hazards: Product will burn under fire conditions. Closed containers may explode due to build up of pressure when exposed to extreme heat.

Hazardous Decomposition Materials: (under fire conditions) Oxides of nitrogen and carbon.

6. ACCIDENTAL RELEASE MEASURES

Cleanup and Disposal of Spill: Biodegradable product. Mop up spill and dispose of by dilution to a sanitary sewer system as permitted by local, state and federal regulations.

Environmental and Regulatory Reporting: Not required.

7. HANDLING AND STORAGE

Minimum/Maximum Storage Temperatures: 39 to 100 °F. Protect from freezing.

HANDLING: AVOID CONTACT WITH SKIN, EYES OR CLOTHING.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

General: These recommendations provide general guidance for handling of this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. When developing safe handling procedures, do not overlook the need to clean and dispose of the material. Waste resulting from the use of this product should be handled in accordance with Section 13: Disposal Considerations.

Exposure Guidelines: Exposure limits are recommended worker breathing limits. The following limits apply to this material:

INGREDIENTS	LIMITS	INGREDIENTS	LIMITS
Water	None established	Monoethanolamine	3 ppm OSHA/PEL
Oleic Acid	None established	Nonylphenoxypolyethanol	None established
2-Propoxyethanol	None established	Quaternary Ammonium Chloride	400 ppm OSHA/TWA
Sodium Dodecylbenzene Sulfonate	None established	DODECYLTHIOETHOXYLATE	None established

8. EXPOSURE CONTROL/PERSONAL PROTECTION, CONTINUED

Engineering Controls: Normal room ventilation.

Respiratory Controls: For reasonable uses of this material, respiratory protection should not be necessary.

Eye/Face Protection: Safety glasses to protect from splashing.

Skin Protection: Rubber or plastic gloves to avoid drying and irritation to the skin.

Work Practice Control: Normal hygiene in the work area should be taken when working with or handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance: Amber liquid.

pH: 10 - 11 as concentrate

Water Solubility: Soluble, may haze slightly

Freezing Point Range: 6 °F

Vapor Pressure: Not established

Percent volatile by volume: Approx. 60 % by volume

Odor: Mild pine odor.

Specific Gravity: 0.98

Melting Point Range: Not available

Boiling Point : Not established

Vapor Density: Not established

V.O.C. (calculated) : 3.14 lbs./ gal or 378.8 grams / l.

10. STABILITY AND REACTIVITY

Chemical Stability:

This material is stable under normal handling and storage conditions as described in Section 7.

Conditions to be avoided: Heat, open flame.

Materials/Chemicals to be avoided: Strong acids, oxidizing agents, aluminum, magnesium, zinc.

Decomposition type: Thermal Oxides of carbon nitrogen and sulfur.

Hazardous Polymerization: WILL NOT OCCUR

Avoid the following to inhibit hazardous polymerization: NOT APPLICABLE

11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation: Irritating to eyes.

Acute Skin Irritation: No test data found for product.

Acute Dermal Toxicity: No test data found for product.

Acute Respiratory Irritation: No test data found for product.

Acute Inhalation Toxicity: No test data found for product.

Acute Oral Toxicity:

LD50 (rat) = 1085 mg / .kg for monoethanolamine

LD50 (rat) = 3089 mg / /kg 2-Propoxy ethanol

LD50 (rat) = 438 mg / kg for Sodium Dodecylbenzene Sulfonate

LD50(rat) = 3.0 gm / kg for Dodecylthioethoxylate hydrocarbonsChronic

LD50 (rat) = 74 gm/ kg for Oleic Acid

LD50(rat) = Not available for Quaternary ammonium chloride

LD50 (rat) = 4 gm / kg for Nonylphenoxypolyethanol

LD50 (rat) = 3200 mg/ kg for terpene

Toxicity: This product does not contain any substances that are considered by OSHA, NTP, IARC OR ACGIH to be a probable or suspected human carcinogens. No additional test data was found for this product.

12. ECOLOGICAL INFORMATION

Ecotoxicological Information: No data found.

13. DISPOSAL CONSIDERATIONS

This product is biodegradable and can be disposed in sanitary sewer system where permitted by local, federal and state regulations.

14. TRANSPORTATION INFORMATION

This product is classified as a combustible liquid for domestic shipments per 49 CFR 173.150 3 (f). It is not regulated as hazardous.

Do not stack cartons more than five high.

15. REGULATORY INFORMATION:

Inventory Issues: All components of this product are listed on the U.S. TSCA list..

16. OTHER INFORMATION

National Fire Protection Association

Hazard Rating, NFPA

Health

2

Flammability

2

Reactivity

0

Special

--

MSDS CHANGES

REV

E

Date

11/17/05

DESCRIPTION OF CHANGE

Reissued

Disclaimer: The information herein is given in good faith but no warranty expressed or implied is made

Prepared By: L&R Manufacturing Company

Date: 03/01/99

Product Name: **HYDRO-SONIC CLEANING SOLUTION NON-AMMONIATED**