



## APPLICATION BULLETIN #50

### TRAFFIC SIGNAL CONTROLS

Imagine trying to recondition a traffic light. L&R Ultrasonic Cleaning Systems make a breeze of this problem.

Simply-

1. Place rack containing parts (relays, flashers, dials, and complete signal controllers) into the first tank filled with #222 Non-Ammoniated Ultrasonic Instrument Cleaning Solution or a water solution of SF-50 Solvent-Free Degreaser Concentrate (heated).
2. Cavitate for 10 minutes. Remove and drain.
3. Place rack into the Auxiliary Pan filled with Instrument Rinsing Solution. If SF-50 Solvent-Free Degreaser Concentrate is used the parts should be rinsed in warm water instead of Instrument Rinsing Solution. Allow to air dry.
4. Place Pan into Ultrasonic Cleaner and cavitate Instrument Rinsing Solution for 6 minutes. Remove and drain. Allow to air dry.

#### EQUIPMENT NEEDED:

Machines & Accessories\*: Suitable sized Ultrasonic Cleaning Unit with Optional Heater if using SF-50 Solvent-Free Degreaser Concentrate, and Stainless Steel Rack or Basket.

Solutions: SF-50 Solvent-Free Degreaser Concentrate (PC 71); #222 Non-Ammoniated Ultrasonic Instrument Cleaning Solution(PC191); Instrument Rinsing Solution (PC194).



*because clean matters*

L&R Manufacturing Company  
577 Elm Street, PO Box 607  
Kearny, NJ 07032-0607 USA  
Tel: 201.991.5330 Fax: 201.991.5870  
[www.LRultrasonics.com](http://www.LRultrasonics.com) [info@LRultrasonics.com](mailto:info@LRultrasonics.com)